



PRIMO

BENEFITS

- **Tested components**
- **Halogen- and PVC-free sockets**
- **Variants with:**
 - **Overvoltage protection, type 3**
 - **Mains and frequency filters for voltage peaks up to 30 MHz**
 - **USB charger with 2.1 A charging current**
- **Available with bigger socket distance, ideal for connecting power supply unit plugs**



Dimensions (W x H x D): see table
Profile: aluminium



Colour variants:

PRIMO

· Supply cable: 1.75m H05VV-F 3G 1.50mm² with right-angled plug with earthing contact

#								
330.073	12	35°	●					690x71x54 mm
330.072	9	35°	●					560x71x54 mm
330.071	6	35°	●					431x71x54 mm
330.070	3	35°	●					304x71x54 mm
331.072	9	35°	●	●	●			690x71x54 mm
331.071	6	35°	●	●	●			560x71x54 mm
331.154	8	35°	●				●	560x71x54 mm
331.012	12	35°						690x71x46 mm
331.011	9	35°						560x71x46 mm
331.010	6	35°						431x71x46 mm
331.000	3	35°						304x71x46 mm
331.007	9	35°		●	●			645x71x47 mm
331.006	6	35°		●	●			515x71x47 mm
331.035	6	35°				●		516x71x83 mm
331.013	6	35°	●	●				474x71x54 mm
331.014	6	35°		●				474x71x54 mm

Master + slave |

333.071	1M+6S	35°		●	●			695x71x47 mm
332.071	1M+6S	35°						573x71x47 mm

ISDN | 1x ISDN input | 3x ISDN output

331.074*	6	35°	●	●	●			645x71x54 mm
----------	---	-----	---	---	---	--	--	--------------

15 mm spacing | Black

331.055	6	90°	●	●	●		●	690x71x54 mm
---------	---	-----	---	---	---	--	---	--------------

85 mm spacing | Black

331.032	5	35°						515x71x46 mm
---------	---	-----	--	--	--	--	--	--------------

Red colour | For IT power circuits

331.040	6	35°						390x71x46 mm
---------	---	-----	--	--	--	--	--	--------------

PRIMO

· Supply cable: 2.0m H05VV-F 3G 1.50mm² with right-angled plug with earthing contact

#		
331.089	1M+5S	670x71x47 mm

Master + slave + foot-operated switch | | 2x red continuous operation socket outlets with earthing contact | 0.1 m with GST18i3 plug | 0.1 m black with GST15/2 plug | Foot-operated switch with 2m supply cable



POWER DISTRIBUTION

* No storage type