

Earthing contact couplings 16 A/250V~

#	
Large version With shutter Shatter-proof plastic With strain relief and protective rubber sleeve Robust H05VV-F 3G 0.75/1.0/1.5 mm ²	
960.103	Black
960.203	White
960.303	Grey
Large version Shatter-proof plastic, with protective rubber sleeve H05VV-F 3G 1.5 mm ²	
912.971	Grey
Small version Shatter-proof plastic H05VV-F 3G 1.5 mm ²	
912.170	Black
912.270	White
912.470	Brown



Euro plugs and couplings 2.5 A/250V~

- Plastic version
- Packed version: contains 3 items in plastic bag – only supplied in packaging unit of 3
- For flat cables up to H05VV-F 2 x 0.75 mm²

#	
Plug	
900.010	Black With screw terminal, packed, 3 items in each bag
900.002	Black With screw terminal, unpacked
900.011	White With screw terminal, packed, 3 items in each bag
900.003	White With screw terminal, unpacked
Coupling	
900.012	Black With screw terminal, packed, 3 items in each bag
900.004	Black With screw terminal, unpacked
900.013	White With screw terminal, packed, 3 items in each bag
900.005	White With screw terminal, unpacked



Safety connector Perilex plug 16 A | 400/230V~

- Side entry, 3-pole + N + PE as per VDE0100/5.73
- IP20

#	
349.203	White



May only be supplied to end user pre-wired | Only to be wired by qualified technicians