



## HC37.53EC

Product	Concealment projecting system (Mirror reflection)
Brand	Pluscreen
Serie	Cinema Mirror
Ref.	HC37.53EC
EAN Code	8435171610123
TARIC Code	HS Code 90079200
Origin	UE
Certifications	TÜV, CE, Rohs, IEC
Recommended uses	To conceal ceiling projectors in meeting rooms, auditoriums, control rooms, home cinema and other video-projection areas, where the end user wants to keep the beauty design of his room when he is not projecting.
Key features	<ul style="list-style-type: none"> <li>••• Compact. It fits in a small space</li> <li>••• Aesthetic. reduce impact</li> <li>••• Quality. Keeping the same image of a direct projection</li> <li>••• Quiet. Avoid the noise of the projector when it is running</li> <li>••• Safe. The projector is it is not accessible against intruders</li> <li>••• Compatible. It allows the use for different projectors, ratio of projection and position of the lens</li> <li>••• Complete. Available accessory to keep the elegance of the installation</li> </ul>

## TECHNICAL DETAILS

<p>Mechanical</p>	<p>Dimensions:</p> <p>Maximum Total Size cm (Included protrusions):  39,5 x 21,0* x 62,5  Motorized Mirror open: 39,5 x 47,5* x 62,5</p> <p>(* )Height of cinema mirror depends on the adjustment of both mirrors</p> <p>Total weight kg.:  12</p> <p>Projector movable Tray:  Size cm: 39x36  Motion H cm: +/-11  Turntable: 90°</p> <p>Adjustable projection mirrors  First face mirrors: 2  Fixed mirror cm: 18x19  Distance bottom mirror – Movable tray cm: 3  Movement V: 3,5cm  Tilt: 40° – 45°</p> <p>Motorized mirror cm: 30x30  Tilt: 50° – 55°</p> <p>Note: the sum of both angles must be 90°</p> <p>Adjustable to different ceiling thickness. (2cm – 3,5cm)  Security accessory to anchorage it to the ceiling  Finished bezel for false ceiling  Material of Housing: Iron Alloy  Included RF Remote control RF: MRF-1RC</p>
-------------------	---

Electrical	Motor Type: Synchro motor RPM: 2 Noise <20 dB Power: 240V AC 50Hz Consumption: 10W
Working conditions	Ratio of projection > 1,5 Offset of projector: Universal. Except 0° Temperature: -10°C ~+50°C. Humidity: 5% to 50% RH (No condensation) Minimum hole dimension to fit the motorized mirror cm: 33,5 x 33,5 Minimum hole dimension to fit HC-635EC (optional) cm: 60x60

## LOGISTIC DETAILS

Package Size and weight	Unit, including package: Size cm: 74 X 48 X 25 Weight kg: 12  Cases per European Pallet 12  Completed EUR Pallet Cases per EUR Pallet: 12 Size cm: 120x80x165 Weight Kg: 170
-------------------------	---

## ACCESORIES

**HC-635EC** Frame kit for Cinema Mirror fixation and closing top  
 Kit Marco is finishing ceiling system  
 Material type: Iron 1,5 mm  
 Color: RAL 9016 white matte

