# •«Х Y U N D Л I

# **OUTDOOR DIGITAL SIGNAGE**

**KIOSK PORTRAIT TYPE SCREEN** 

CLASS

32″

H325SSV

MODEL

# Broadcast your branding with Hyundai Digital Signage!

HYUNDAI's Outdoor Digital Signage represents state-of-art display technology for any outdoor environment. Meeting the highest industrial standards they are provide a high degree of operational reliability and superior quality image, which are essential preconditions for attracting the attention of your target audience.

## **KEY FEATURES**

- Special DOOH LCD Panel
- All Weather Capable (IP66)
- Sunlight Readable
- Anti-Vandal Protection
- Non AC cooled system
- Auto Brightness Control
- Remote Control (RS232)
- Easy to Service with Front Door Open
- Cabinet Housing Color: RAL7040



• XI Y U N D / I

# **OUTDOOR DIGITAL SIGNAGE**

CLASS

MODEL

H325SSV 32"

# SPECIFICATIONS

Model		H325SSV
Panel	Screen Size (diagonal)	32"
	Active Display Area (inch   mm)	27.496 x 15.465   698.40 x 392.85
	Resolution	1920 x 1080
	Aspect Ratio	16:9
	Display Colors	16.7 M
	Brightness (cd/m²; typ.)	2000
	Contrast Ratio	1300:1
	Response Time (ms; GTG)	25
	Viewing Angle	178°/178°
	Lifetime (hours)	30,000
	Backlight type	LED
Input	VGA (15pin D-Sub)	1
	HDMI	1
	DVI	1
	RS-232C	1
Power	Operating Voltage	100 - 240 VAC
	Consumption (typ.)	145W (Without PC)
	Consumption per nits (max.)	0.12 W
	Heater Block (with PC Case)	850W / Peak 1.2 KW
Features	Auto Cooling System	Yes
	Auto Heating System	Yes
	Anti-Vandal Glass	Yes (8mm = 3mm+3mm)
	Anti Reflection Coating	Yes
	Auto Brightness Sensor	Yes
Operation	Temperature (°C)	-30 ~ 50
	Humidity (%)	20 - 80
	Storage (°C)	-40 ~ 60
	OSD Language	10 Lang
Approvals	Ingress Protection	IP66
Dimension	Set (W x H x D), inch   mm	26.59 x 66.93 x 5.91   675.3 x 1700 x 150
Weight	Set (lb   kg)	T.B.D
Mounting (Bo	ttom mounting)	M10 wedge anchor (6 pcs)
Computer		Option

### FEATURES

#### All Weather Capable

Equipped with an intelligent cooling and heating system, HYUNDAI's Outdoor Displays are well suited for withstanding any weather conditions from -30 $^{\circ}C$  to +50 $^{\circ}C$ .


#### Sunlight Readable

HYUNDAI provides special displays which are based on the Optical Bonding for installatons in environment with the birghtest lightning conditions. Make your messages and images clear and readable under even bright sunlight.

#### **Anti-Vandal Protection**

Thanks to a special tempered security glass. HYUNDAI's Outdoor Displays are protected against any vandalism attacks using Anti-Vandal glass bonding technique improving in durability from outside damage.

### DIMENSIONS



Specifications and design are subject to change without notice. See our website for detailed information.

#### HEAD OFFICE - HYUNDAI IT CO., LTD.

S-20 Garden5 Tool 8F, Chungmin-ro, Songpa-gu, Seoul, 138-962 Korea Tel. +82 70 7008 0110 email : prio123@hyundaiit.com www.hdit.co.kr

#### HYUNDAI IT AMERICA CORP.

2051 Junction AVE., Suite 112 San Jose, CA 95131, USA Tel. +1 408 954 8920 email : sales@hyundaita.com www.hyundaiit.com

#### HYUNDAI IT EUROPE GMBH

Siemensstrasse 22, 63225 Langen, Germany Tel. +49(0) 6103-38878-100 email : info@hyundaiit.eu www.hyundaiit.eu

#### UPDATE : MAR. 2015

#### HYUNDAI IT JAPAN

Kawaziri Bldg 2F, 534 Waseda Tsurumaki-cho, Shinjuku-ku, Tokyo, Japan Tel. +81-3-6273-9652 email : sales@hyundaiit.co.jp www.hyundaiit.com