# • 🛠 Y U N D / I

## **OUTDOOR DIGITAL SIGNAGE**

**KIOSK PORTRAIT TYPE SCREEN** 

CLASS

55″

H557SSV

MODEL

### Broadcast your branding with Hyundai Digital Signage!

HYUNDAI's Outdoor Digital Signage represents state-of-art display technology for any outdoor environment. Meeting the highest industrial standards they are provide a high degree of operational reliability and superior quality image, which are essential preconditions for attracting the attention of your target audience.



- Special DOOH LCD Panel
- All Weather Capable (IP66)
- Sunlight Readable
- Anti-Vandal Protection
- Non AC cooled system
- Auto Brightness Control
- Remote Control (RS232)
- Easy to Service with Front Door Open
- Cabinet Housing Color: RAL7040



• X Y U N D A I

### **OUTDOOR DIGITAL SIGNAGE**

CLASS

**H557SSV** 55″

#### **SPECIFICATIONS**

Model		H557SSV
Panel	Screen Size (diagonal)	55″
	Active Display Area (inch   mm)	47.62 x 26.787   1209.6 x 680.4
	Resolution	1920 x 1080
	Aspect Ratio	16:9
	Display Colors	16.7 M
	Brightness (cd/m <sup>2</sup> ; typ.)	2500
	Contrast Ratio	5000:1
	Response Time (ms; GTG)	8
	Viewing Angle	178°/178°
	Lifetime (hours)	50,000
	Backlight type	LED
Input	VGA (15pin D-Sub)	1
	HDMI	1
	DVI	1
	RS-232C	1
Power	Operating Voltage	100 - 240 VAC
	Consumption (typ.)	500W (Without PC)
	Consumption per nits (max.)	0.16 W
	Heater Block (with PC Case)	850W / Peak 1.2 KW
Features	Auto Cooling System	Yes
	Auto Heating System	Yes
	Anti-Vandal Glass	Yes (8mm = 3mm+3mm)
	Anti Reflection Coating	Yes
	Auto Brightness Sensor	Yes
Operation	Temperature (°C)	-30 ~ 50
	Humidity (%)	20 - 80
	Storage (°C)	-40 ~ 60
	OSD Language	10 Lang
Approvals	Ingress Protection	IP66
Dimension	Set (W x H x D), inch   mm	38.0 x 85.8 x 6.3   965 x 2180 x 160
Weight	Set (lb   kg)	328.49   149
Mounting (Bo	ttom mounting)	M10 wedge anchor (6 pcs)
Computer		Option

#### **FEATURES**

#### All Weather Capable

Equipped with an intelligent cooling and heating system, HYUNDAI's Outdoor Displays are well suited for withstanding any weather conditions from  $-30^{\circ}$ C to  $+50^{\circ}$ C.

#### Sunlight Readable


HYUNDAI provides special displays which are based on the Optical Bonding for installatons in environment with the birghtest lightning conditions. Make your messages and images clear and readable under even bright sunlight.

#### Anti-Vandal Protection

Thanks to a special tempered security glass. HYUNDAI's Outdoor Displays are protected against any vandalism attacks using Anti-Vandal glass bonding technique improving in durability from outside damage.

#### DIMENSIONS

[unit: mm | [inch]]



Specifications and design are subject to change without notice. See our website for detailed information.

HEAD OFFICE - HYUNDAI IT CO., LTD.

5F, 36, Sangil-ro 10-gil, Gangdong-gu, Seoul, 05288 Korea Tel. +82 70 7008 0151 E-mail: ssoh@hdi.co.kr www.hdit.co.kr

HYUNDAI IT AMERICA CORP.

2051 Junction AVE., Suite 112 San Jose, CA 95131, USA Tel. +1 408 954 8920 email : sales@hyundaita.com www.hyundaiit.com

HYUNDAI IT EUROPE GMBH

Borsig Str. 11-13 65205 Wiesbaden, Germany Tel. +49(0) 6122-70342-10 email : info@hyundaiit.eu www.hyundaiit.eu

UPDATE : JUL. 2016