

PT-102VN

1:2 Composite Video Distribution Amplifier





The PT-102VN is a distribution amplifier for composite video or SDI signals. It takes one input, provides correct buffering and isolation and distributes the signal to two identical outputs.

FEATURES

- High Bandwidth 430MHz (−3dB).
- Level (Gain) and EQ (Peaking) Controls.
- Ultra Compact Pico TOOLS™ 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter.



PT-102VN

TECHNICAL SPECIFICATIONS

INPUTS: 1 composite or SDI video, $1Vpp/75\Omega$ on a BNC connector. OUTPUTS: 2 composite or SDI video, $1Vpp/75\Omega$ on BNC connectors.

MAX. VIDEO OUTPUT: 2Vpp.
VIDEO BANDWIDTH (-3dB): 430MHz.
DIFF. GAIN: 0.05%.
DIFF. PHASE: 0.05Deg.
K-FACTOR: <0.05%.
S/N RATIO: 76.1dB.

CONTROL: Gain: -1.2 to +6dB; EQ.: 0 to +7.5dB @50MHz via trimmers accessible from the front panel.

POWER SOURCE: 12V DC, 30mA.

DIMENSIONS: 6cm x 6.5cm x 2.5cm (2.36" x 2.56" x 1") W, D, H.

WEIGHT: 0.14kg (0.31lbs) approx.

ACCESSORIES: Power supply.

OPTIONS: RK-4PT 19" rack adapter.

