



PT-572HDCP+

DVI over Twisted Pair Receiver



The PT-572HDCP+ is a DGKat™ twisted-pair receiver for DVI signals. The PT-571HDCP converts the DVI to twisted pair signal and the PT-572HDCP+ converts the twisted pair signal back to a DVI signal.

FEATURES

- **Max. Data Rate** - 1.65Gbps.
- **HDTV Compatible.**
- **HDCP Compliant.**
- **DGKat™ Signal Integration** - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables. We strongly recommend using Kramer DGKat™ cables designed specifically for optimum performance.
- **System Range** - Up to 90m (295ft) at SXGA, or up to 30m (98ft) at UXGA on shielded BC-DGKat524 cable.
Up to 90m (295ft) at SXGA, or up to 70m (230ft) at UXGA on shielded BC-DGKat623 cable.
Up to 100m (330ft) at SXGA, or up to 80m (265ft) at UXGA on shielded BC-DGKat7a23 cable.
- **Cable** - Requires STP (shielded twisted pair) cable. For optimum range and performance, use Kramer's BC-DGKat524, BC-DGKat623 or BC-DGKat7a23 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges.
- **EDID PassThru** - Passes EDID signals between the source and display.
- **Power Connect™ System** - A single connection to the transmitter or the receiver powers the system when the devices are within 270ft (90m) of each other.
- **Ultra-Compact PicoTOOLS™** - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter.



PT-572HDCP+

TECHNICAL SPECIFICATIONS

- INPUTS:** 1 DGI twisted pair on an RJ-45 connector.
- OUTPUTS:** 1 DVI, 1.2Vpp on a DVI Molex 24-pin female connector, DDC signal 5Vpp (TTL).
- BANDWIDTH:** Supports up to 1.65Gbps.
- POWER SOURCE:** 12V DC, 250mA.
- DIMENSIONS:** 6.2cm x 5.2cm x 2.4cm (2.4" x 2.1" x 1") W, D, H.
- WEIGHT:** 0.14kg (0.3lbs).
- ACCESSORIES:** Power supply, mounting bracket.
- OPTIONS:** RK-4PT 19" rack adapter.

