



VS-211HA

2x1 Automatic HDMI Standby Switcher

| HDMI | HDCP Compliant



The VS-211HA is a high-performance automatic standby switcher for HDMI video and unbalanced stereo audio signals. The VS-211HA can be used as a manual 2x1 switcher or automatic switcher. The switcher uses a priority input or last connected input

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)
- HDMI & HDCP Compliant
- HDTV Compatible
- Advanced Auto Switching - Based on video clock detection
- Automatic Output Shutdown - If no input signal is detected after a configurable idle period
- 3D Pass Through
- EDID PassThru - Passes EDID signals from display to source
- Audio Return Channel (ARC) Pass Through
- Parallel Unbalanced Stereo Audio Switching
- Contact Closure Remote Control - For manual switching override
- DIP-Switches - For setting the switching mode



KRAMER

TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors, 2 unbalanced stereo audio on 3.5mm mini jacks
OUTPUTS:	1 HDMI connector, 1 unbalanced stereo audio on a 3.5mm mini jack
MAX. DATA RATE:	6.75Gbps (2.25Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP
CONTROLS:	Contact closure on a 3pin terminal block, 2 priority DIPswitches
INDICATORS:	ON and active input LEDs
POWER CONSUMPTION:	5V DC, 120mA (without load), 350mA (fully loaded)
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.6kg (1.3lbs) approx
INCLUDED ACCESSORIES:	Power supply
OPTIONS:	RK3T 19" rack adapter

