

MonLines MLE675S myTVLift wall mount 675 with housing



Description

The myTVLift with housing is a simple and stable TV lift with a load capacity of 40 kg. The operation of the quiet monitor lift is done manually or by remote control.

Key features

TV Lift

Mounting:	electric wall mount
VESA Standard:	75x75, 100x100, 200x100, 200x200, 300x200, 300x300, 400x200, 400x300, 400x400 mm
Capacity:	40 kg
Extension height:	670 mm
Height adjustable:	Infinitely variable manually or remote control
Brake:	Double-acting brake for increased self-locking ability
Ambient temperatures:	+5°C to +40°C
Finish:	Silver oder black

Remote control

Wireless:	3x AAA Battery
Service:	Hand control to control 1 or 2 References
Distance range:	Approximately 6 m

MonLines MLE675S myTVLift wall mount 675 with housing

Key features

Control Box

Connection:	Up to 2 actuators / columns
Line voltage:	230 V AC, 50Hz oder 120 V AC, 60 Hz
Power consumption:	Power consumption in standby mode is due to the toroidal transformer only 1.6 watts
Overload protection:	(EOP), current limiting
Brake:	Soft-Start/Stop-Funktion
Strain relief:	For power supply
Automatically detects:	Automatically detects the number of connected drives Automatic detection of the connected drive type
Duty cycle:	Max. 10% ~ 6 minutes per hour and 2 minutes of continuous operation at full load
Tested:	According to EN 60335-1, UL 962 and the Australian Standard AS/NZS3197

Panel

Transmission:	Infrared
Operating device:	For a single channel or parallel systems
Cable:	1.580 mm straight, black cable with modular jack connector

