


NOVUS MY arm 2.0



- Infinitely height adjustable 2-part monitor support arm with VESA Standard 75/100
- New cross joint with pivot function for working in vertical format
- Closed mount for a tidy rear side
- Mounting of flat screens up to 5 kg
- Rotatable and swivelling
- Range: 415 mm
- Balance mechanism at the front joint for optimum monitor positioning
- Enables horizontal positioning of the screen
- Includes two cable clips
- MY base as a mandatory extension


Version	Art.No.	EAN Code
 Silver	911+2019+000	4009729068977



This standard mount allows monitors with VESA standard 75x75 or 100x100 to be easily attached. The value indicates the hole spacing in mm.



The value indicates the maximum bearing capacity of the supporting element or the maximum weight of a mountable monitor in kg.



The value indicates the scope of the product in mm



This machine bears the GS approval of product safety.



The quality statement „German Engineering“ ensures that a product was developed according to German quality standards by our engineering experts. All Novus products carrying the „German Engineering by Novus“ signet are manufactured in our own plants around the world by our own workforce, managed and supervised by our headquarters in Germany.

Novus Notebook plate






Novus offers a warranty of 5 years when handled in a proper manner.



The quality statement „German Engineering“ ensures that a product was developed according to German quality standards by our engineering experts. All Novus products carrying the „German Engineering by Novus“ signet are manufactured in our own plants around the world by our own workforce, managed and supervised by our headquarters in Germany.

- notebook plate for MY-arms 2.0 and Clu-arms
- Support platform (404 x 288 mm) for regular and large notebooks
- Grommet in the support plate
- Obligatory supplement is a Clu- or MY 2.0-arm

Version	Art.No.	EAN Code
 White	795+9161+000	4009729075357
 black	795+9168+000	4009729075364
 Silver	795+9169+000	4009729073636