





65

75

86"

# Most natural and accurate writing experience

The Predia Touch Swift 4 touchscreen takes collaboration to a new level, in businesses, governments, and schools. It offers the most natural and accurate writing experience, unprecedented speed and optimal connectivity.

# Seamless connectivity

The display features multiple USB Type-C connection with multiconnectivity. With one cable, you can connect your laptop and all other devices like a webcam, microphone, and speakers instantly.

# 🔄 Beautifully clear image

Razor-sharp image thanks to an anti-reflective finish and 400 nits brightness. The 4K display offers a perfect viewing experience in any room. Even in well-lit meeting rooms.

# Intelligent Touch technology

Write your ideas on the screen naturally and accurately thanks to intelligent writing features such as near-zero delay, pressure sensitivity and palm rejection support.

# Top performance

The screen features the secure Android 13 operating system and a super-fast 8-core CPU. This makes the screen 50% faster than previous generations.

# E Powerful sound across the room

The Predia Touch Swift 4 features a powerful sound bar at the top of the screen. The sound is spread throughout the entire room, giving everyone the best sound experience.

# ᅙ Ultra-fast built-in Wi-Fi

Easily connect the screen to the latest Wi-Fi 6E by installing the Wi-Fi module at the bottom of the screen.

# 🖉 Energy-efficient

The Predia Touch Swift 4 has low power consumption thanks to its eco-friendly design and the latest technologies.

# Maximum security

Thanks to the Predia Home OS operating system and the powerful Android 13 module, the screen will have optimal security and the latest updates for years to come.

# ᡖ Maximise productivity

Take collaboration to the next level by connecting up to three displays with the Type-C and HDMI outputs.

#### predia.eu



	65"	75"	86"
Display size	05	75"	00
Model	Predia Touch Swift 4 65	Predia Touch Swift 4 75	Predia Touch Swift 4 86
Display Technology	LCD	- Liquid Crystal Display Direc	tLED
Panel type		IPS ADS	
Aspect ratio	16:9		
Resolution	3.840	0 x 2.160 - 4K Ultra High Defir	nition
Response time		8 ms	
Refresh rate	60 Hz		
Active screen size	1209.6 × 680.4 mm	1428.48 × 803.52 mm	1895.04 × 1065.96 mm
Brightness		400 cd/m2	
Contrast ratio	4.000:1	5.000:1	4.000:1
Pixel Pitch	0.315 × 0.315 mm	0.372 × 0.372 mm	0.4935 × 0.4935 mm
Colour depth	1.07B (10bit)		
NTSC	72%		
Air Gap	2nd generation zero bonding		
Glass plate	Anti-reflection Nano-technology / antibacterial		
Glass hardness	Mohs 7		
Viewing angle	178° (H/V)		
Lifetime		≥ 40.000 hour	

# Operating system

Operating system	Android™ 13.0
Software version	Predia Home OS 2.0
RAM	8 GB
ROM	64GB
CPU	High-End (A76x4+A55x4)
GPU	High-End (Mali G610 MP4)
Light sensor	Yes
Motion sensors (PIR)	Optional
NFC	Optional
Air Quality Meter	Optional
Over-the-Air-Updates (OTA)	Yes (5 year support)



# Interactive touch

Technology	3th Generation IR Pro
Recognition	Finger, passive pen
Accuracy	± 1 mm
Touch points	50
Minimum object size	2 mm
Auto-calibration	Yes
Palm recognition	Yes
Simultaneous multi-colour writing	Yes
Writing in different thicknesses	Yes
Intelligent object recognition	Yes
Response time	≤ 2.5ms
Supported compatibility	Windows 11 / Windows 10 / Windows 8 / Windows 7 / Linux / Mac / Android / Chrome

# Audio

Speakers	Full-fledged Soundbar at top of the screen (2.2 Sound)
Frontspeakers	2x 20 Watt
Subwoofer	2x 10 Watt
Amplifier power	108 Watt 8 Ω

# Microphones

Туре	Wide-area microphones
Number of microphones	8
Automatic switching	Yes
Deactivatable	Yes



# Connections

HDMI 2.0	4 (up to 4K@6ohz, HDCP 2.3, CEC)
HDMI OUT	1 (up to 4K@60hz)
USB 2.0	1
USB 3.0	4 (auto switch)
USB Type-C (full function)	1 x (100 Watt , USB 3.2, Video DP1.2, Audio, Touch , LAN) 1 x (15 Watt, USB 3.2, Video DP1.2, Audio, Touch, LAN)
USB Typ -C out	1 (4K@60hz)
USB B Touch	2
DP IN	1 (DPI 2)
AUDIO IN	1
AUDIO OUT	1
SPDIF	1
RS232	1
LAN Port IN	1 (1000 MBit/s)
LAN Port OUT	1 (1000 MBit/s)
PC-Modul Slot	80-Pins OPS Slot

General information	65"	75"	86"
Product dimensions L×H×D	1488 × 908 × 86 mm	1709.4 × 1031 × 85.7 mm	1957 × 1171 × 86 mm
Packaging dimensions L×W×H	1628 × 208 × 1005 mm	1863 × 225 × 1148 mm	2110 × 225 × 1283 mm
"Distance from touchscreen to wall (Predia Wallmount) "	116 mm	115.7 mm	116 mm
VESA Pattern	600 × 400	800 × 400	800 x 600
Net weight	38 kg	51 kg	63 kg
Packed weight	48 kg	60 kg	80 kg
Certificates	CE: EMC + LVD / / RoH	S / REACH / WEEE/ FCC-IC / CB /	/ RCM / TÜV Rheinland



# Environmental conditions

Operating temperature	0°C - 40°C
Operating humidity	10% - 90% RH (no condensation)
Storage temperature	Min 20°C tot 40°C
Storage humidity	10% - 90% RH (no condensation)
Maximum operating height	5000 meter

Electrical characteristics	65"	75"	86"
Current voltage	1	00 V - 240 V ~ 50 Hz / 60 Hz 4.	5 A
Nominal energy consumption	109.2 W	128.9 W	142.5 W
Standby consumption		≤ 0.5 W	


# Accessoires

Power cable	1 x 3 m
USB Touch cable (Type A-B)	1 X 3 M
HDMI-cable	1 X 3 M
WiFi Module	1 (802.11 AX - WiFi 6E)
Passive pens	2
Remote control	1
Batteries	2 (AAA)





# Technical drawings

Predia Touch Swift 4, 65"



Predia Touch Swift 4, 75"










Predia Touch Swift 4, 86"



╎<u>╶╶╴╴╴╴╴</u>┶╴<u>└╴</u>╼╾╶┥</u>╵



