



Wireless Conferencing System

The Connect is an all-in-one wireless conferencing system with camera streaming and integrated Speakerphone for optimal conferencing in small to medium-sized rooms. Wirelessly share your screen at high quality and stream your camera with sublime sound experience.

4K Wireless Casting

Effortlessly share your screen on the big display with just the click of a button. No software is required - simply connect your laptop to the speakerphone for a seamless wireless casting experience.

8-Mic Array

Experience crystal-clear audio with far-field voice pickup from all directions and echo cancellation. Engage everyone in the conversation without missing a word.

Camera Streaming

Make your webcam wireless by connecting it to the receiver. Access 1080P video wirelessly from your seat effortlessly, and keep your video conference space clutter-free.

Vocal Enhancement

The powerful speaker adjusts to enhance human voice against background noise and delivers immersive sound effects for every meeting.

Speakerphone

Microphone

Built-in Microphone	8 MEMS Microphone for 360-degree pickup
Pick-up Distance	4 m
Signal/Noise Ratio (SNR)	94dB SPL@1KHz 65dB(A)
Sensitivity	94dB SPL@1KHz -37±1dB FS
Acoustic Overload Point	132.5dB FS, 10%THD@1KHz
Frequency	20Hz - 8000Hz
Duplex	Yes
Beamfoming	Yes
Automatic Noise Suppression	Yes
Acoustic Echo Cancellation	Yes
Automatic Gain Control	Yes

Speaker

Speaker	4Ω3W
Speaker Size	50mm
Sensitivity	81 dB SPL +/-3dB SPL@1m, 1W
Signal/Noise Ratio (SNR)	80dB
Frequency Range	100Hz-20kHz
Max. Sound Pressure Level	85dB SPL@1m@3W
Background Noise	<28dB@1m

Screen Casting

Max. Screen Output Resolution	3840x2160 @30FPS
-------------------------------	------------------

Camera Streaming

Max. Output Resolution	1920x1080 @30FPS
Support Camera Type	UVC camera
Format Supported	H.264

Wi-Fi

Authentication protocol	SRRC
Wireless Transmission Protocol	Quick UDP Internet Connections
Transmission Distance	10M

Others

I/O Interface	Speakerphone Sender: Type C PD + DP ALT Receiver: HDMI x1; TYPE C PD ; USB A 3.0
Operating System	Win 10/ 11; Mac 10.8 and Later
Product Dimensions	Speakerphone: 180 x 81 x 32mm / 7.09 x 3.19 x 1.26" Receiver: 102 x 45 x 20mm/ 4.02 x 1.77 x 0.79"
Product Weights	Speakerphone: 385g / 13.58oz Receiver: 70g / 2.47oz
Package Contents	TecLines Connect (speakerphone and receiver), 2m Type-C to Type-C cable, 1.5m HDMI Cable, 0.3m USB switch cable

Webcam

Camera

Sensor	SONY IMX415 Sensor CMOS 1/2.8", 8.46M pixel, with high dynamic range and noise reduction
USB Video Class	UVC 1.0
Supported Video Resolution	MJPEG/H.264/H.265/YUV/NV12 @30fps 3840x2160 / 2560x1440 / 1920x1080 / 1280x720 / 1024x576 / 960x540 / 800x448 / 640x360 / 320x180 / 960x720 / 800x600 / 640 x 480 / 480x270 / 352x288 / 320x240
Maximum Video Resolution & FPS	USB3.0 - 3840x2160@30fps , USB2.0 1280x720@30fps
Viewing Angle	120°
Focus	50cm -
F No.	F2.5
Zoom	5x Digital Zoom
Tilt Angle	±14°
Auto-Framing	Yes Auto White
Balance	Yes
Auto Exposure	Yes
Auto Backlight Compensation	Yes

Microphone

Built-in Microphone	Dual Electret Microphones
Pick-up Distance	Effective: 0-4m Maximum: 8m
Signal/Noise (Amplitude)	f=1KHz.Pin=1 Pa A=curve 65dB
Sensitivity (Sound Pressure Level)	f=1KHz.Pin=1 Pa -30±2dB SPL 100dB FS
Double Talk	Yes Active Noise Reduction & echo cancellation Yes
Auto Gain Control	Yes
ESD Standard	Contact discharge to 4KV, Air discharge to 8KV
Eye Diagram	USB3.0 Eye Diagram Test Passed

Others

Privacy Shutter	Yes
Connectivity	USB-C to USB-A
Powered By	USB 3.0 (5V 900ma)
Operating System	Win 10/11, macOS 10.8 or above, Android, Linux
Mount Type	Clip / Tripod
Cable	USB-C to A Cable (2-meter)
Package Contents	TecLines C570, USB cable, remote control, AAA battery for remote